



SAFETY DATA SHEET
JETCEM WATERPROOFING RAPID SET CEMENT

Page 1
Issued: 03/11/2010
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product name: JETCEM WATERPROOFING RAPID SET CEMENT
Product code: JETWAT3
Company name: EVERBUILD BUILDING PRODUCTS LTD
SITE 41, KNOWSTHORPE WAY
CROSS GREEN INDUSTRIAL ESTATE
LEEDS
WEST YORKSHIRE
LS9OSW
ENGLAND
Tel: 0044 113 240 3456
Fax: 0044 113 240 0024
Emergency tel: 0044 113 240 3456 (office hours only)
Email: pault@everbuild.co.uk

2. HAZARDS IDENTIFICATION

Classification under CHIP: Risk of serious damage to eyes.
Classification under CLP: Eye Dam. 1. Causes serious eye damage.
Workplace exposure limit: This product does not have a workplace exposure limit.
PBT: This substance is not identified as a PBT substance.
Directive 1999/45/EC: This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.
Other hazards: Contains Chromium VI. May produce an allergic reaction

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ORDINARY PORTLAND CEMENT 30-50%
• HIGH ALUMINA CEMENT 10-30%

4. FIRST AID MEASURES

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.
Exposure hazards: In combustion emits toxic fumes.
Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Do not create dust.

Environmental precautions: Do not discharge into drains or rivers.

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

Storage conditions: Keep container tightly closed. Store in original containers between +5 and +25°C.
Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: ORDINARY PORTLAND CEMENT
UK - 8 hour TWA: 5mg/m³ (Respirable dust)

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter. Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Powder

Colour: Grey

Odour: Odourless

Evaporation rate: Negligible

Solubility in water: Slightly soluble

Relative density: 1.8

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Moist air. Humidity.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute effects: Risk of serious damage to eyes.

11. TOXICOLOGICAL INFORMATION (SYMPTOMS)

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** There may be soreness and redness of the mouth and throat.
- Inhalation:** Exposure may cause coughing or wheezing.

12. ECOLOGICAL INFORMATION

- Persistence and degradability:** No data available.
- Bioaccumulative potential:** No data available.
- Other adverse effects:** No data available.
- PBT identification:** This substance is not identified as a PBT substance.

13. DISPOSAL CONSIDERATIONS

- Disposal operations:** Dispose of according to local or national legislation
- Disposal of packaging:** Dispose of as normal industrial waste.
- NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: Not Classified.

IMDG / IMO

UN no: Not Classified.

IATA / ICAO

UN no: Not Classified.

15. REGULATORY INFORMATION (CHIP)

Hazard symbols: Irritant.

- Risk phrases:** R41: Risk of serious damage to eyes.
- Safety phrases:** S2: Keep out of the reach of children.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S39: Wear eye / face protection.
- S46: If swallowed, seek medical advice immediately and show this container or label.
- Haz. ingredients (label):** ORDINARY PORTLAND CEMENT; HIGH ALUMINA CEMENT
- Note:** The regulatory information given above only indicates the principal regulations

specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

15. REGULATORY INFORMATION (CLP)

Hazard statements: H318: Causes serious eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

* indicates text in the SDS which has changed since the last revision.

Risk phrases used in s.3: R41: Risk of serious damage to eyes.

Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.

Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause skin and respiratory irritation, dermatitis or burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.