



WALLBARN MEGAPADS & TD MEGAPADS
WEIGHT TOLERANCE TEST DATASHEET

Description	Extra-large and extended thread Adjustable Pedestals with optional slope correctors		
Height	Weight Tolerance		
10-20mm * 22-30mm * 28-37mm *	Maximum Load: 11,493 N = 1,171kg End of Linear Behaviour: 6,700N = 683kg		
35-50mm 50-75mm 75-120mm 115-220mm 215-320mm 315-420mm 415-520mm 515-620mm 615-720mm 715-820mm 815-920mm 915-1020mm	Maximum Load: 20,713 N = 2,057kg End of Linear Behaviour: 15,300N = 1,560kg CATAS Test Score 179112 / 1		
Slope correctors	1% 2% 3%		
Material	Polypropylene		
Diameter of Head Piece	150mm		
Diameter of Screw	140mm		
Diameter of Base	200mm * 150mm		
	Score		Test Method
Melt Flow rate	14-16 Gr / 10'		ASTM D 1238
Weight / density	0.99-1.04 Gr / cm ³	ASTM D 792 Method A	
Softening point with load of 5kg (VICAT test)	>75 °C	ASTM D 1525	
Heat Deflection Test with load of 1820 kPa	> 90 °C	ASTM D 648	
Coefficient of elasticity	1600 Mpa	ASTM D 790	
Impact resistance (Izod test - at 23°C)	>40 J/m	ASTM D 256	
Impact resistance (Izod test - at minus 20°C)	>20 J/m	ASTM D 256	
Max Weight Tolerance at minus 40°C	27.830 N	CATAS 179112 / 1	
Fire classification	All MEGAPADS supports are classified as "EUROCLASS E" according to EN 13501-1:2009		

Wallbarn Ltd. Unit 16 Capital Business Centre, 22 Carlton Road, CR2 OBS
 Tel: +44 (0)208 916 2222 Fax: +44 (0)208 916 2223 Email: sales@wallbarn.com
 Web: www.wallbarn.com