

## Safe-Seal C250

### Ductile iron C250 single seal access covers

Wrekin's range of single-seal BS EN 124:2015 C250 Group 3 Manhole Covers have been designed to combine high strength and light weight. They include additional features such as a single seal labyrinth and safety enhancements.



Illustrated: DMS1C3/6060/K



-  For use in a Group 3 Class C250 environment
-  All fully comply with BS EN 124:2015 and are Kitemarked by BSI
-  A patented safety keyway prevents accidental disengagement during the lifting operation. Also compatible with standard D400 lifting keys.
-  Incorporates a single seal labyrinth arrangement to help prevent odour escapes and water ingress
-  Manufactured from strong and highly durable ductile iron
-  Slide out cover designed for ease of removal

### Range details

Wrekin product code	Clear opening size (Cx D mm)	Frame depth (mm)	Over frame size (Ax B mm)
DMS1C3/4545/K	450 x 450	75	555 x 555
DMS1C3/6045/K	600 x 450	75	705 x 555
DMS1C3/6060/K	600 x 600	75	705 x 705
DMS1C3/60D/K	600 dia	75	692 x 692
DMS1C3/7560/K	750 x 600	75	850 x 700
DMS1C3/9060/K	900 x 600	75	1000 x 700

Available options: Special badging, ventilation holes, locked covers, sealing plates, rubber seals and safety grilles.

## SAFE-SEAL C250



1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves that the above data is current.
3. Wrekin cannot be held responsible for the performance of these products as conditions of use are beyond our control.
4. Installation details are available on request.