


D400 Gully Grates

Ductile iron D400 Group 4 catch pit

Wrekin's range of BS EN 124:1994 D400 Group 4 Gully Gratings have been designed to provide optimum strength whilst maximising the available drainage area.




Illustrated: DGT0D4/6060/KHA

- D400** For use in a Group 4 Class D400 carriageway environment
- HA104/09** Complies fully with UK Highways Authority specification HA 104/09
- Up to 2020cm² waterway area
- All fully comply with BS EN 124:1994 and are Kitemarked by BSI
- Manufactured from strong and highly durable ductile iron
- Three point suspension on covers for non-rock stability

Range details


| Wrekin product code | Clear opening size (Cx D mm) | Frame depth (mm) | Over frame size (AxB mm) | Waterway area (cm ²) |
|---------------------|------------------------------|------------------|--------------------------|----------------------------------|
| DGT0D4/6060/KHA | 600 x 600 | 100 | 750 x 750 | 2020 |
| DGT0D6/6060/KHA | 600 x 600 | 150 | 750 x 750 | 2020 |

Available options: Screw-locking to deter unauthorised access to the gully chamber (will require standard extended-shank socket set tooling to engage/disengage locking screw).



Ductile iron D400 Group 3 gully grate

Wrekin's BS EN 124:1994 D400 Group 3 Gully Grating has been designed to provide optimum strength whilst maximising the available drainage area.




- D400** For use in a Group 3 Class D400 carriageway environment
- HA104/09** Complies fully with UK Highways Authority specification HA 104/09
- Manufactured from strong and highly durable ductile iron
- All fully comply with BS EN 124:1994 and are Kitemarked by BSI
- Up to 1200cm² waterway area
- Captive hinges reduce theft risk whilst allowing easy lifting for gully cleaning

Range details

| Wrekin product code | Clear opening size (Cx D mm) | Frame depth (mm) | Over frame size (AxB mm) | Waterway area (cm ²) |
|---------------------|------------------------------|------------------|--------------------------|----------------------------------|
| DGH0D4/5035/K1* | 500 x 350 | 100 | 440 x 655 | 1200 |
| DGH0D4/3631/K | 365 x 310 | 100 | 510 x 420 | 850 |

* Screw-locking to deter unauthorised access to the gully chamber (will require standard extended-shank socket set tooling to engage/disengage locking screw).



1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
2. It is the responsibility of all users to satisfy themselves that the above data is current.
3. Wrekin cannot be held responsible for the performance of these products as conditions of use are beyond our control.
4. Installation details are available on request.