Block pavior access covers

100mm galvanised mild steel cover and frame

This comprehensive range of recessed manhole covers and frames are for use in areas of block paving where it is desirable to have continuity of surface finish and pattern. They are recessed 100mm for use with up to 80mm block pavior and galvanised to BS EN ISO 1461. The table below lists the main standard sizes with non standard sizes available on request. The lifting keyways are all reinforced to help avoid distortion.



- Manufactured from strong and highly durable mild steel
- Steel frames have superior adherence to bedding mortar than plastic frames
- · Reinforced lifting keyways to help avoid distortion when lifting
- Galvanised to BS EN ISO 1461

Range details

Clear opening (mm)	Tray depth (mm)	Over frame size (mm)	Overall frame depth (mm)	GLVW	Load duty description	SMWL pneumatic	FACTA Class (comparative)	Wrekin product code
300 x 300	100	435 x 340	105	10tn	Light/Medium	2.5tn	AAA	C291M/030030
450 x 450	100	585 x 485	105	10tn	Light/Medium	2.5tn	AAA	C291M/045045
600 x 450	100	655 x 600	105	10tn	Light/Medium	2.5tn	AAA	C291M/060045
600 x 600	100	745 x 640	105	10tn	Light/Medium	2.5tn	AAA	C291M/060060
750 x 600	100	790 x 750	105	10tn	Light/Medium	2.5tn	AAA	C291M/075060
750 x 750	100	900 x 788	105	10tn	Light/Medium	2.5tn	AAA	C291M/075075
900 x 600	100	945 x 750	105	10tn	Light/Medium	2.5tn	AAA	C291M/090060
450 x 450	100	600 x 518	105	25tn	Medium	5tn	В	C291N/045045
600 x 450	100	640 x 600	105	25tn	Medium	5tn	В	C291N/060045
600 x 600	100	750 x 665	105	25tn	Medium	5tn	В	C291N/060060
750 x 600	100	825 x 740	105	25tn	Medium	5tn	В	C291N/075060
900 x 600	100	970 x 750	105	25tn	Medium	5tn	В	C291N/090060
600 x 450	100	665 x 600	105	44tn	Heavy	11tn	D	C291X/060045
600 x 600	100	750 x 665	105	44tn	Heavy	11tn	D	C291X/060060
675 x 675	100	825 x 740	105	44tn	Heavy	11tn	D	C291X/067067
750 x 600	100	820 x 755	105	44tn	Heavy	11tn	D	C291X/075060
750 x 750	100	895 x 815	105	44tn	Heavy	11tn	D	C291X/075075
900 x 600	100	1100 x 760	105	44tn	Heavy	11tn	D	C291X/090060





- 1. Wrekin Products Ltd is continually seeking to improve our products and therefore reserves the right to alter product specifications without prior notice.
- 2. It is the responsibility of all users to satisfy themselves that the above data is current.
- Wrekin cannot be held responsible for the performance of these products as conditions of use are beyond our control.
- 4. Installation details are available on request.