



Product Fiche

Supplier Name or Brand	Arada Ltd
Product Code	FARRINGTON-L-BLACK-EU-G2
Energy Efficiency Class	A
Direct Heat Output	10.6 kW
Energy Efficiency Index	102.7
The useful energy efficiency at nominal heat output and at minimum load	77.0%

Specific precautions that shall be taken when the local space heater is assembled, installed or maintained: *Product should be installed in accordance with local building regulations. Appliance will become very hot during use.*

Features

Flexifuel	Yes
Stove Type	Freestanding
Ecodesign Ready	Yes
Suitable for Smoke Control Areas	Yes
Suitable for direct air connection	Yes
Suitable for non-combustible 12mm hearth	Yes
Underhearth temperature	64 °C
Weight (packed kg)	140 Kg

Dimensions

Width	615 mm
Height	666 mm
Depth	426 mm
Flue Diameter	152 mm
Added height when on stand	796 mm
Height on pedestal	959 mm
Height on log store	996 mm
Height to centre of rear flue	548 mm
Depth from back to centre of rear flue	112 mm
Ideal log length	500 mm

Performance - Wood & Solid Fuel

	Wood Fuel	Smokeless Solid Fuel
Energy Efficiency Class	A	E
Nett Efficiency	77 %	79.8 %
Nominal Output	10.6 kW	12.1 kW
DIN+ particulate	13 Nmg/m3	8 Nmg/m3
Mean Co Emission(@13% O2)	0.08 %	0.04 %
Mean Co2 Emission(@13% O2)	12 %	13.7 %
Mean NOx Emission(@13% O2)	75 Nmg/m3	66 Nmg/m3
Mean OGC Emission(@13% O2)	63 Nmg/m3	6 Nmg/m3
Flue Gas Mass Flow	8.5 g/s	7.2 g/s
Flue Gas Temperature	337 °C	377 °C

Minimum Distance To Combustibles

To Rear	To Rear (twin wall)	To Side	To Side (twin wall)
600 mm	430 mm	500 mm	600 mm