



Dune eVo

NEW BEGINNINGS



In every sector from transport to retail, and in every environment from hotels and hospitals to schools and workplaces, Dune eVo is designed to meet all your project needs. Dune eVo is 100% recyclable for never ending value and Cradle to Cradle Certified™ to meet your sustainability targets.

Key features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Fully painted, reinforced edges for a more robust tile and greater durability
- Easy to handle and re-engineered for a better, easier fit

- Enhanced acoustical absorption performance of 0.60 α_w for better acoustic comfort
- Mix and match modules for increased flexibility and a more complete project solution
- First tile and grid system to gain C2C certification
- 30 year system warranty

Application areas


























Ideal for every space.



Dune eVo

Inspiring Great Spaces®

Armstrong®
CEILING SOLUTIONS

EDGE DETAIL	BOARD		TEGULAR		MICROLOOK 90							
												
THICKNESS (mm)	15		15		15							
MODULES (mm)	600 x 6005460M 1200 x 6005461M		600 x 6005462M 1200 x 6005463M		600 x 6005464M 1200 x 6005465M							
SUSPENSION SYSTEMS	Prelude 24 XL ² /TLS Prelude 24 Sixty ² XL ² /TLS		Prelude 24 XL ² /TLS Prelude 24 Sixty ² XL ² /TLS		Interlude HRC XL ² Silhouette 6 mm XL ² Prelude 15 TL/XL ²							
COLOURS			 Global White									
SUSTAINABILITY			 44%		 A	 E1						
ACOUSTICS			 EN ISO 10848-2 & EN ISO 717-1		 EN ISO 354 & EN ISO 11654							
			D _{nfw}	α _w	Class	NRC	125	250	Hz α _p			
							125	250	500	1000	2000	4000
Board / Tegular / MicroLook 90			34 dB	0.60	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50
FIRE REACTION			EEA Euroclass A2-s1, d0 EN 13501-1									
OTHER PERFORMANCES & FEATURES	 85%		 99% RH						 LIFETIME guarantee		 BIM READY	
	 λ = 0.060 W/m K		 ≈ 3.6 kg/m ²						 30 YEAR system guarantee			
CUSTOM OPTIONS	 Colours*		 Dimensions									