# **Gyproc WallBoard**

# Safety Data Sheet

# **Health & Safety**

## 1. Identification of the substances / preparation and company

## 1.1 Product identifier: Gyproc WallBoard

#### 1.2 Relevant identified uses:

Gyproc plasterboards are used as internal linings in buildings.

# 1.3 Details of the supplier of the safety data sheet:

**Supplier** British Gypsum

East Leake Loughborough Leicestershire LE12 6HX

Telephone 0844 800 1991

Email bgtechnical.enquiries@bpb.com

This information reflects typical values and is not a product specification.

#### 2. Hazards identification

THE MOST IMPORTANT HAZARDS ARE:

#### 2.1 Classification of the substance or mixture:

This product is <u>not</u> classified as dangerous according to EU regulation 1272/2008 or 1999/45/EEC and their amendments.

Dust from mixing or sanding may irritate the respiratory system, skin and eyes.

# 3. Composition / information on ingredients

**General composition:** Calcium sulphate dihydrate encased in paper liners, natural constituents may include minor amounts of quartz. Small quantities of chopped glass fibre, microsilica and vermiculite may be added, with starch, foam and dispersants.

Any board may contain small quantities of chopped man-made mineral fibre and microsilica.

# 4. First aid measures

# 4.1 Description of first aid measures:

**Eye contact** P305/ - In case of contact with eyes, rinse

P313 immediately with plenty of water

and seek medical advice.

**Skin contact** P264 - After contact with skin, wash

immediately with plenty of soap

and water.

<u>Ingestion</u> P331 - If swallowed, do not induce vomiting,

seek medical advice immediately and

show this document.

P301/ - If swallowed rinse mouth with water

P330 (only if the person is conscious).

**Inhalation** P304/ - In case of accident by inhalation,

P340 remove casualty to fresh air and keep

at rest.

General Get medical attention if any

symptoms persist.

# 5. Fire fighting measures

#### 5.1 Extinguishing media:

Suitable extinguishing media - water, foam, carbon dioxide or dry powder.

## 5.2 Special hazards arising from the substance or mixture:

The product does not pose a fire hazard. However, some packaging materials may burn.

#### 5.3 Advice for fire fighters:

Use protective equipment appropriate for surrounding materials.

#### 6. Accidental release measures

# 6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective clothing as described in section 8 of this safety data sheet.

#### 7. Handling and storage

#### 7.1 Precautions for safe handling:

<u>Manual handling</u> – Sheets of plasterboard can be unwieldy, use an appropriate lifting technique. The weight of each sheet can vary between products. For manual handling purposes assume the following:

# Gyproc WallBoard weights:

<i>7</i> i		O				
Board thickness mm	Board width mm	Board length mm	Board weight kg	Pallet weight tonnes		
9.5	900	1800	10.2	1.1		
9.5	1200	2400	19.9	1.8		
12.5	900	1800	13.9	1.1		
12.5	900	2400	18.5	1.5		
12.5	1200	2400	2.4	1.7		
12.5	1200	2500	25.5	1.8		
12.5	1200	2700	27.6	1.7		
12.5	1200	3000	29.8	1.5		
12.5	1200	3600	37.2	1.5		
15	900	1800	17.2	1.0		
15	900	2400	22.9	1.4		
15	1200	2400	29.7	1.5		
15	1200	2700	34.6	1.4		
15	1200	3000	38.4	1.5		

**NB** All weights are approximate.

Mechanical handling – The dimensions of the pallet vary depending on the product size. To avoid potentially overloading a lift truck, it is important that any effect on load centres is considered. The nominal weight of each palletised load is given within the weights table in this section of this document.

Plasterboards will not support body weight in between rafters, joints or frame members.



# **Health & Safety (continued)**

# 7.2 Conditions for safe storage, including any incompatibilities:

<u>Storage</u> – Store on pallets supplied in dry conditions. To maintain stability, place pallets on firm level ground, and ensure that stacks are both level and vertical.

NB When working with individual boards, only work from a single pallet, not a stack.

<u>Pallet stacking heights</u> – The maximum stack heights on level concrete floors and vertical stacks are as follows:

Board width mm	Board length mm	Pallet stack height packs
900	1800, 2400	4
1200	1800	5
1200	2400, 2500, 2700	6
1200	3000	7
1200	3600	10

#### 7.3 Specific end use:

<u>Use</u> – Minimise dust generation when sawing or sanding in poorly ventilated places. Avoid eye contact - see Section 8 for recommended personal protective equipment, and Section 3 for hazards identification.

# 8. Exposure control / personal protection

# 8.1 Control parameters:

#### Workplace exposure limit

Substance	Total inhalable	Respirable
Plaster	10mg/m³ 8hr TWA	4mg/m³ 8hr TWA
Quartz (silica)	-	0.1mg/m³ 8hr TWA
Man Made Mineral Fibres (MMMF)	5mg/m³ 8hr TWA (gravimetric method)	-

# 8.2 Exposure controls:

Process conditions - Use engineering controls to reduce air contamination to permissible exposure levels. Engineering measures - All handling to take place in well ventilated areas.

#### Personal protection

**Respiratory** P284 - Use only in well-ventilated areas.

Wear eye / face protection. Face masks to *EN 149 FFP2*.

**Skin** P303 - Wear suitable protective clothing.

Eye P305/ - Wear eye / face protection. P313 Eye protection to *BS EN 166*.

#### 9. Physical and chemical properties

# 9.1 Information on basic physical and chemical properties:

<u>Appearance</u> Flat sheet boards in different widths and

thicknesses, with a square or tapered edge.

## 10. Stability and reactivity

#### 10.1 Reactivity:

No specific reactivity hazards associated with this product.

## 10.2 Chemical Stability:

Stable under normal temperature conditions.

## 10.3 Possibility of hazardous reactions:

None in normal conditions of use.

## 10.4 Conditions to avoid:

None

# 10.5 Imcompatible materials:

None.

#### 10.6 Hazardous decomposition products:

None in normal conditions of use.

#### 11. Toxicology information

## 11.1 Information on toxicological effects:

No known toxicological effects.

#### 12. Ecological information

Stable product with no known adverse environmental effects.

# 13. Disposal consideration

#### 13.1 Waste treatment methods:

Gypsum, the main raw material for plasterboard, is a sulphate but is classified as non-hazardous. Waste from gypsum plasterboard products is fully recyclable. For more information contact the British Gypsum Plasterboard Recycling Service Team on 0800 6335040 or visit the British Gypsum website at british-gypsum.com

#### 14. Transport information

Not classified as hazardous for transportation.

## 15. Regulatory information

This product is classified according to EU regulation 1272/2008 and its amendments.



# **Health & Safety (continued)**

#### 16. Other information

Control of Substances Hazardous to Health Regulations
The Manual Handling Operations Regulations
HSE Guidance Note EH40: Workplace Exposure Limits
Gypsum Wastes – Environment Agency Information Sheet
The British Gypsum White Book
The British Gypsum Site Book
The British Gypsum website: british-gypsum.com

*Note to user:* This Safety Data Sheet does not constitute a workplace risk assessment for COSHH.

There are a number of situations where the approach to manual handling of British Gypsum products should be considered. For further guidance, please refer to the Manual Handling Section of the **Site Book** or the Manual Handling Guide, available to download from british-gypsum.com.

Date of previous version: November 2006.

"Gyproc", "Thistle", "Gypframe" and "Glasroc" are all registered trademarks of BPB United Kingdom Limited. "Isover" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of Saint-Gobain Isover and "Artex" is a registered trademark of BPB United Kingdom Limited.

BPB United Kingdom Limited is a limited company registered in England under company number 734396, having its registered office at Saint-Gobain House, Binley Business Park, Coventry, CV3 2TT, UK. BPB United Kingdom Limited trades as British Gypsum for part of its business activities.

British Gypsum reserves the right to revise product specification without notice. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work. For a comprehensive and up-to-date library of information visit the British Gypsum website at: british-gypsum.com. For information about products supplied by Artex Limited or Saint-Gobain Isover please see their respective websites.

"British Gypsum" is a registered trademark of BPB United Kingdom Limited.

Telephone: 0844 800 1991 Fax: 0844 561 8816

Email: bgtechnical.enquiries@bpb.com

Training enquiries: 0844 561 8810

© British Gypsum May 2015 SDS-001-05



