

Declaration of Performance Number: 500 Gauge Vapour Control Layer

1. Unique identification code of the product-type:

500 Gauge Virgin Grade VCL

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing – Plastic and rubber vapour control layers – Definitions and characteristics (EN 13984)

3. Name and contact address of the manufacturer:

Novia Ltd Unit 12 Heronden Road Park Wood Industrial Estate Maidstone Kent ME15 9YR

4. Name of the authorized representative whose mandate covers the tasks specified in Article 12, Paragraph 2: Adrian Chisholm

5. System of assessment and verification of constancy of performance of the construction product:

3

6. Notified body:

British Board of Agrement (BBA) NB 0836

7. Declared Performance

Essential	Technical	Bottom	Top tolerance	Unit	Test standard
Characteristics	Performance	tolerance			
Length	50	50	55	m	EN1848-2
Width	2.7	2.63	2.77	m	EN1848-2
Mass per unit	115	100.6	131.4	g/m ²	EN1849-2
area (weight)					
Tensile MD	101	86	116	N/50mm-1	EN12311-2
Tensile CD	93	79	107	N/50mm-1	EN12311-2
Water vapour transmission properties	0.68			g/m². day	EN1931
Water tightness 2k Pa	Pass	-	-	-	EN1928:2000

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance (DOP) is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by

ACW	18.09.2014
Adrian Chisholm, Product Manager	Date
Novia Ltd	