

# No. 06 SIMPLICITY

## Internal Doors

A statement door that doesn't make a fuss.



### A minimal approach

Clean and contemporary lines and a subtle primed white finish make this door perfect for those looking to set a minimalist tone.

### A real heavyweight

This door's solid core gives it a reassuringly premium feel that you'll experience every time it closes with a satisfying noise. Look no further for an exceptionally dependable door.

### Add your touch

This door is supplied primed white, so you can add your own unique flair to mirror your personality.

### Find yours

Available in many designs, with a mixture of styles including panel and glazed options.



### Features & benefits:

- Stylish, minimalist design
- Sleek smooth finish
- Factory primed white
- Sound reducing solid core
- 5-year guarantee
- Toughened safety glass on glazed doors

# DOOR DESIGNS



Shaker 1 Panel   Shaker 4 Panel   Shaker 1 Light Obscure   Shaker 4 Light Clear   Shaker 10 Light Clear   Shaker 15 Light Clear   Aston 3 Panel   Aston 3 Light Clear   Cottage   Cottage Vertical Etch   Worcester   Worcester 3 Light Clear   Ladder   Ladder 1 Light Clear

Width (mm)	Height (mm)	Depth (mm)
610*	1981	35
686	1981	35
762	1981	35
838	1981	35

## OPTIONAL PRIMED PAIR MAKER



\* 610 not available on Worcester glazed / cottage vertical etch

<b>Material specification</b>	Primed MDF Facing, Solid Particle Board Core Ladder Doors - Lightweight Particle Board Core
<b>Finish</b>	White primed, requiring final top coat
<b>Glass specification</b>	4mm (Clear/Obscure - depending on design) Toughened Glass
<b>Accessory options</b>	Primed pair maker optional extra
<b>Decoration requirements</b>	It is essential that the door is completely finished on the two faces and all FOUR edges plus any cut-outs for locks, handles and hinges etc. Prior to finishing or sealing, lightly sand any handling marks. Usually 3 top coats are satisfactory but we strongly recommend you that you treat this door in accordance with the paint manufacturer's instructions. A light sanding between coats will provide the best finish. Adequate drying time must be allowed between each coat. Failure to seal the doors accordingly will invalidate any claims.
<b>Storage</b>	Doors must be stored flat in cool, dry conditions avoiding direct contact with sunlight before the door has been finished.
<b>Trimming allowance</b>	If the door is to be reduced in size, an equal amount of timber should be trimmed from either side or bottom, this must never exceed 10mm in total, 5mm each side and 6mm from the bottom. We do not recommend trimming the top of the door.
<b>Guarantees</b>	5 Year Manufacturing
<b>Sustainability</b>	FSC Mix 70%