



SFC-241KBIM-A

SANTEC 2MP analogue 4-1 IR bullet camera
2,7-12mm, IP-66, 12VDC

PRODUCT DESCRIPTION

► Application:

SANTEC SFC day/night bullet camera for indoor and outdoor applications, IP-66 classification. Due to the built-in IR-LEDs (range: up to 30m) and the 6mm lens, the camera is suitable for day as well as for night applications. The camera has an excellent resolution of 1080p at 25 fps. The camera comes with a wall bracket with integrated cable management.

► Technical specifications:

Type	IR bullet camera
Video signal	CVBS (analogue)
Sensor	1/2.9" CMOS
Sensor type	Progressive scan CMOS
Resolution	960H
Effective pixel	1920x1080
Signal processing	Digital (DSP)
Synchronisation	Intern
S/N ratio (dB)	< 65dB
Lens mount	Intern
Iris control	Auto/manual
Lens type	DC vario lens
Focal length	2,7 - 12 mm / F1.4
Angle of view (horizontal)	67° - 17°
IR cut filter	IR-Cut filter (mechanical)
Sensitivity (Lux)	0,02 Lux (color) / 0,0 Lux (IR on)
Automatic gain control (AGC)	AGC

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



► Technical specifications:

Digital noise reduction (DNR)	2D
Shutter (sec.)	1/25 - 1/100.000
White balance	AWB / manual
Backlight compensation	BLC, HLC, WDR
Wide dynamic range (WDR)	DWDR
Day/night mode adjustment	Auto / manual
Camera adjustments	OSD -> recorder menu
Auto focus	No
Focus control	Manual
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Motion detection (zones)	Yes (via recorder)
Privacy zones	Yes, 8 zones
Camera title	Yes
Video output	BNC, 75 Ohm 1 Vpp
Switch input contacts	No
Switch output contacts	No
Control interface	HDCVI (coax)
Classification	IP-66
Vandal-proof	No
Installation	Wall mount, ceiling mount and pole mount
Camera mounting	Screw mounting
Housing colour	White
Housing material	Aluminium
Integrated IR-LEDs	Yes
IR range (m)	up to 30
IR wave length	850
Voltage	12 V DC
Max. Power consumption (watt)	2,5
DORI max. (Detect-Observe-Recognize-Identify)	125m - 50m - 25m - 13m
DORI min. (Detect-Observe-Recognize-Identify)	49m - 20m - 10m - 5m
Operating temperature (°C)	-20 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxDxH (mm)	90,4x213x90,4
Weight	0,55 Kg
Identifier	CE, FCC, RoHs, UL
Specials	Multi-norm: HDCVI, AHD, TVI, CVBS



SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

Note:

The range of the built-in IR-LEDs strongly depends on the location and the surroundings. Strongly absorbent surfaces, e.g. dark, rough structures (floor, lawn or asphalt), may lead to a considerable reduction of the maximum range. Camera works in CVBS mode.

► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SNCA-MK-4537	Adapter/Junction box for SCC-241KBIM and SCC-251KBIA
SNCA-PM-4660	Pole Mount adapter up to 127 mm and SNCA-JB-4640 and SNCA-WM-4642 (SNC-211RSIA)
SFB-100	SFC controller switch for HD-CVI, AHD, TVI and CVBS
SNCA-MK-4537	Adapter/Junction box for SCC-241KBIM and SCC-251KBIA