



SNC-441FDIF

SANTEC 4 MP Mini IP-dome camera
2,8 mm fix lens, IR-LED, IP-66.

PRODUCT DESCRIPTION

► Application:

SANTEC SNC-441FDIF is an 3-axis dome camera with integrated IR-LEDs and it is the perfect solution for all 24/7 indoor and outdoor applications. This IP camera has a weather-proof housing (IP-66) and is vandal-proof (IK10). Thanks to 4 megapixel resolution, the images are very clear hence no detail is undetected. Due to the auto focus lens and the web interface the camera is easy to adjust. The camera comes with features such as 3DNR for noise reduction, Wide Dynamic Range (WDR), PoE and micro-SD card slot, to name but a few.

► Technical specifications:

Type	IP day/night dome camera
Sensor type	1/3" Progressive Scan CMOS
Picture resolution (pixel)	4 MP (2688x1520)
Video codec	H.264, H.265, MJPEG, H.264+, H.265+
Max. frame rate (fps)	25 fps@4MP
Number of video streams	3 (1x Main, 2x Sub)
Lens mount	Intern
Iris control	DC
S/N ratio (dB)	< 50dB
Lens type	Fixlens
Focal length	2,8 mm, F2.0
Angle of view (horizontal)	104°
Sensitivity (Lux)	0,08lx (color)
Sensitivity (Lux)	0Lux (IR on)
IR cut filter	IR-Cut filter (mechanical)
Day/night mode adjustment	Auto / color / B/W

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► **Technical specifications:**

Automatic gain control (AGC)	Yes
Digital noise reduction (DNR)	3DNR
Shutter (sec.)	1/3 - 1/100,000
White balance	Auto / sunny / night / outdoor / manual
Backlight compensation	BLC, HLC, WDR(120dB)
Wide dynamic range (WDR)	120 dB WDR (True WDR)
Digital zoom	16x, adjustable
Mirroring (vertical)	Yes
Picture flip (horizontal)	Yes
Privacy zones	Yes, 4 zones
Region of Interest (ROI)	Yes, 4 zones
IVA via ONVIF Motion	Yes
People counting (IVA+)	Yes
Heatmap (IVA+)	Yes
Tripwire (IVA)	Yes
Intrusion (IVA)	Yes
Tampering Alarm	Yes
Scene change (tampering)	Yes
IVS Missing / Added	Yes
Audio detect (IVA)	Yes
Face detect (IVA)	Yes
Motion detection	Yes, 4 zones
Motion detection (zones)	Yes
Camera title	Yes
Video output	Yes
Audio support	Yes
Audio in-/outputs	No
Audio codec	G.711a / G.711Mu / AAC / G.726
Alarm contacts I/O	No
Alarm management	HTTP, FTP, SMTP, ONVIF
Schedule	Yes
Management software support	Many VMS
Supported browser	Internet Explorer 11
BURG-WÄCHTER cloud	Yes
Smartphone App	BurgCam App
Security features	HTTPS, SSL, IP Filter
Supported protocols	HTTP, TCP, NTP, IPv4, IPv6, DHCP, TELNET, ONVIF, FTP
Supported software standards	ONVIF, PSIA, CGI
Internal memory	Micro SD (optional), max. 128 GB
Video Content Analytics (VCA)	Tripwire, Intrusion, Face detect, etc.
Ethernet connector	RJ-45
Ethernet standards	10/100Base-T
Classification	IP-66, IK10
Vandal-proof	Yes, acc. to IK10

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



► Technical specifications:

Heater	No
Installation	Wall and ceiling mount
3 axis	yes
Camera mounting	Screw mounting
Housing colour	White
Housing material	Metal / Plastic
Integrated IR-LEDs	Yes, Smart IR, off, manual
Wavelength IR-LED	850 nm
IR-LED illuminant	10
IR distance (m. ca.)	20
DORI max. (Detect-Observe-Recognize-Identify)	63m - 25m - 13m - 6m
Voltage	12 V DC, PoE
PoE standard	IEEE 802.3af
Max. Power consumption (watt)	4,5
Operating temperature (°C)	-30 to +60
Storage temperature (°C)	-30 to +60
Rel. humidity (%)	Max. 95, non-condensing
Dimensions DxH (mm)	106 x 50,3
Weight	400 g
Identifier	CE, RoHS
Items included in delivery	CD, software, quick user guide

► Note:

SD card is not included.

► Recommended Accessories

SNPS-12D2	SANTEC stabilized power supply 12 V DC, 1.5 A, plug / adapter
VCA-12V-1.5ASA	SANTEC stabilized power supply unit 230V AC/12V DC, 1.5 A, with plug /adapter
SANPOWER-MS01L	1-channel PoE power supply 48V DC
SNCA-WM-204W	Wall bracket for SNC-431FEIF, SNC-431FDIF
SNCA-MK-4533	Adapter/Junction box Suitable for: Please see accessory selection
SNCA-PM-4661	Mastadapter inkl. Spannbänder von 80 bis 130 mm