



SPVR-3411

HD Penta-brid digital videorecorder 4 ch
HDCVI/AHD/TVI/CVBS/IP

PRODUCT DESCRIPTION

► Application:

This pentabrid digital video recorder of the SPVR series is able to record video signals of HD-CVI, TVI, AHD cameras as well as analogue CVBS cameras - in real-time at 25 fps on every channel in full resolution up to 2MP(CVI,AHD,TVI), 5MP(IP) resp. 960H in analogue mode. The recorder is also able to process images of max. 2 IP cameras in pentabrid mode or 6 in IP mode only. The recorder is network-capable and has manifold functions such as integrated motion detection, intelligent video analysis, camera signal detection or recording by schedule. Moreover, several recorders can be managed using an administration software. The recorder can remotely be accessed by the BURG CAM App.

► Technical specifications:

Type	HD pentabrid digital video recorder
Video inputs	4 x BNC
Video signal	HD-CVI, TVI, AHD, CVBS (analogue)
Max. resolution AHD, TVI	2 MP (1920 x 1080)
Max. resolution CVBS	960H
Internal operating system	Embedded LINUX
Video outputs (BNC)	No
Max. IP channels	6 (without BNC inputs)
Max. resolution IP camera	5 MP (2560 x 1920)
Split mode	1 /4
Audio inputs	1 x Cinch
Audio outputs	1 x Cinch
Alarm inputs	No
Alarm outputs	No

SANTEC BW AG
An der Strusbek 31, 22926 Ahrensburg, Germany
Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Max. HDD capacity	6 TB
Max. number of HDDs (internal)	1 x SATA
External HDD possible	No
RS-232 interface	No
RS-422 interface	No
RS-485 interface	No
USB interface	USB 2.0
USB ports	2 x Back side
Ventilation	Fan
Spot monitor outputs	Yes, VGA or HDMI
Number of supported monitors	1x HDMI, 1x VGA
Split mode spotmonitor	Yes
Internal RAID	No
DVD-RW	No
Export interface	USB/network
Control panels (external)	PC-mouse
Remote control	No
Number of Ethernet ports	1
Ethernet connector	RJ-45
Ethernet speed	10 / 100 / 1000 Mbit (Gigabit)
Ethernet standards	100/1000M Base-T
Compression (video)	H.264
Compression (audio)	G.711
Max. frame rate (fps)	25 fps
Alarm recording (dig. input)	No
Motion recording	Yes
Digital input recording	No
Manual recording	Yes
Permanent recording	Yes
Schedule recording	Yes
Live picture	Yes
Mega pixel camera support	Yes, 5MP
Display split	1/4
Face detect (IVA)	Yes, on channel 1
Intelligent Video Analysis (IVA)	Yes, 1 channel in CVI, AHD, TVI, CVBS mode
Presence (trip wire)	Yes
Object Apear and disappear (IVA)	Yes
Missing/abandoned object detection	Yes
Digital output notification	Yes
Audio notification	Yes
CMS notification	Yes
E-mail notification	Yes
E-map notification	Yes over VMS and mobile app.

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Monitor notification (Popup)	Yes
PTZ notification	Yes
Snapshot notification	Yes
Push-Notification	Yes via mobile App. (Pro version!)
Motion detection	Yes
Camera occlusion detection	Yes
Lost signal detection	Yes
Pre-alarm recording	Ja, einstellbar bis zu 30 S.
Post-alarm recording	Yes, adjustable up to 300 s.
Watermark	Yes
Picture data export	USB / network
Intelligent search	Yes
Intelligent search criteria	date/time, camra, alarm, motion
Password protection	Yes
Log files	Yes
Hidden camera recording	No
Supported OS	Windows 8, Windows 10
Supported browser	Internet Explorer 11
Management of IP devices	Yes
DynDNS support	Yes
UPNP support	Yes
Preset positions	Depends on camera
PTZ control	Yes, via HD-CVI and IP
Remote connections	Yes
Max. remote connections	128
User management	Yes
ONVIF/PSIA	ONVIF 2.4.1, CGI Conformant
Time synchronisation	Yes
DHCP support	Yes
Access	Browser / Client SW / Mobile App
Supported software for remote access	Web PlugIn, BW-IP-CVI-VMS, Burg Cam App
Cloud service	Yes, BURG-WÄCHTER cloud
Transmission speed (network)	max. 1000 Mbit/S.
Firmware upgrade	Network / USB
Housing colour	White
Max. Power consumption (watt)	10 (without HDD)
Voltage	12 V DC using external power supply 230VAC
Operating temperature (°C)	-10 to +55
Rel. humidity (%)	Max. 95, non-condensing
Dimensions WxHxD (mm)	205 x 211 x45
Weight	0,5 Kg
Identifier	CE, FCC, RoHS
Items included in delivery	RC,power supply, power cord, mouse,software

SANTEC BW AG
 An der Strusbek 31, 22926 Ahrensburg, Germany
 Tel.: +49 4102 4798 0, Fax: +49 4102 4798 10
 santec_info@burg.biz, www.santec-video.com



Our products undergo constant development. Please refer to the price list for our most up-to-date product program. Errors and omissions excluded. No responsibility accepted for accuracy of images.

► Technical specifications:

Specials 4-Eyes-Login, HD-CVI, TVI, AHD, CVBS

► Note:

It is recommended to use a USV system.

► Weitere Bilder:



► Recommended Accessories

SANSTORE-STICK	4GB USB stick to backup recorded data
KOAX-0.6/100	Coaxl cable 0.6/3.7, 75 Ohm for indoor usage, 100 m ring
HDD-1000HV	HDD for DVR/NVR, 1 TB SATA 24/7 tested
HDD-2000HV	HDD for DVR/NVR, 2 TB SATA 24/7 tested
HDD-4000HV	HDD for DVR/NVR, 4 TB SATA 24/7 tested
HDD-6000HV	HDD for DVR/NVR, 6TB SATA 24/7 tested