



TECHNICAL INFORMATION SHEET

700758 Epsom Oak

Parquet Collection



Product Information

Product Name Epsom Oak
Product Code 700758

Collection Parquet
Construction Engineered
Size 20 x 100 x 500mm

Pack Size 0.5
Grade Rustic

Product Details

Surface Brushed **Finish** Natural Oil Grade Rustic **Profile** T&G Edge Bevelled **Pattern** Block Width 100mm Length 500mm **Thickness** 20mm Wear Layer 6mm

Backing 14mm Birch Plywood

Top Layer Oak

Grading Information

Rustic grade has the potential to include all characteristics across the majority of boards with knots appearing in varying sizes as well as many levels of natural colour variation in the timber to be expected. A varying amount of sapwood is possible, checks that are likely to be present will be filled in a colour to complement the natural look of the timber.

Installation Method

Floated No
Secret Nailed No
Stuck Down Yes
Underfloor Heating Yes

Technical Information

Formaldehyde Emissions E1
Pentachlorophenol <0.1ppm

Emissions

Slip Resistance 96
Fire Classification Cfl-s1
Thermal Conductivity 0.11 m2K/W
Moisture Content 8% (+/-2%)

Responsible Certification Please ask a member of the

team

Installation and Warranty

Atkinson & Kirby recommend all floors should be installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions found on our website.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice to third parties. To confirm the latest information, please speak to a member of the team.



