



TECHNICAL INFORMATION SHEET

900300 Hampstead Oak

Parquet Collection



Product Information

Product NameHampstead OakProduct Code900300CollectionParquetConstructionEngineeredSize11 x 70 x 500mm

Pack Size 1.68
Grade Select

Product Details

Surface Smooth

Finish Natural Oil Protect

Grade Select Profile T&G

Edge Square Edge

Pattern Block
Width 70mm
Length 500mm
Thickness 11mm
Wear Layer 3.6mm

Backing Spruce Staves

Top Layer Oak

Grading Information

Select grade is likely to contain some boards that have a higher number of knots than Prime, and you should also expect some of these knots to be larger in size. There is a possibility of some sapwood and small cracks and filler are likely to be present. A greater level of colour variation in the timber is to be expected.

Installation Method

Floated No
Secret Nailed No
Stuck Down Yes
Underfloor Heating Yes

Technical Information

Formaldehyde Emissions E1

Pentachlorophenol Not Detectable

Emissions

Hardness Rating 34 - 41
Slip Resistance R10
Fire Classification Cfl-s1

Thermal Conductivity

0.078 m²K/W

Moisture Content

7% +/-2%

Domestic Warranty

LEED Certification

Yes

EPD Certification

Yes

Responsible Certification Please ask a member of the

team

Installation and Warranty

Atkinson & Kirby recommend all floors should be installed by a competent installer. Atkinson & Kirby warranties apply only to floors that have been installed according to our fitting instructions found on our website.

This technical information sheet was compiled and written by Atkinson & Kirby. At the time of publication all information is specified correctly. The company reserves the right to change the specification of this product at any time without prior notice to third parties. To confirm the latest information, please speak to a member of the team



